

The Vivanco PROMOSTICK is the unique element in the presentation of bulk items and packaged goods at the P.O.S.

- Gives flexibility to bulk presentation with Euro hole design (bin, rack) and reduces "rummaging" at the P.O.S.
- Replaces the usual sleeve and fixes the products
- Offers efficient presentation at low costs
- Gives outstanding price/performance ratio



Audio connections

RCA connection, stereo
2x RCA plug <-> 2x RCA plug

- For connection of 2 devices with RCA sockets

PS L301/12
EDP-No. 22185
ctn qty. 10 / 1.2m

PS L 302
EDP-No. 19318
ctn qty. 10 / 2.5m

PS L 307
EDP-No. 19361
ctn qty. 10 / 5.0m

PS L310
EDP-No. 19367
ctn qty. 10 / 10.0m



RCA extension, stereo
2x RCA plug <-> 2x RCA socket

- For extension of RCA connections

PS L 316
EDP-No. 19319
ctn qty. 10 / 5.0m



Connection RCA / 3.5mm
2x RCA plug <-> 3.5mm plug

- For connection of devices with a 3.5mm socket and devices with RCA sockets

PS L 509
EDP-No. 19320
ctn qty. 10 / 1.5m

PS L539
EDP-No. 19720
ctn qty. 10 / 5.0m



3.5mm connection,
3.5mm plug <-> 3.5mm plug

- For connection of 2 devices with 3.5mm sockets

PS L510
EDP-No. 19719
ctn qty. 10 / 1.5m



Audio connections

3.5mm extension

3.5mm plug <-> 3.5mm socket

- For extension of connections between devices with 3.5mm sockets

Optical fibre connection

Toslink <-> Toslink

- For connection of devices with optical in-/outputs

Power supply lead

Euro plug -> IEC 320 C7

- For connection of small electrical devices to the mains socket

PS L 500

EDP-No. 19368

ctn qty. 10 / 1.5m

PS L501

EDP-No. 19369

ctn qty. 10 / 2.5m



PS L1115

EDP-No. 19411

ctn qty. 10 / 1.5m



PS L VN125

EDP-No. 19833

ctn qty. 10 / 1.25m



Video connections

Scart connection, 21pin.

Scart plug <-> Scart plug

- For connection of 2 devices with Scart sockets
- Fully shielded

PS VK 17/12

EDP-No. 22191

ctn qty. 10 / 1.2m

PS VK 18

EDP-No. 19360

ctn qty. 10 / 3.0m

PS VK 17/5

EDP-No. 19330

ctn qty. 10 / 5.0m

PS VK17/10

EDP-No. 19331

ctn qty. 10 / 10.0m



Scart connection, 21pin.

Scart plug <-> Scart plug

- All pins connected, gold plated
- For connection of 2 devices with Scart sockets
- Fully shielded
- Colour: black

PS VK17/12G

EDP-No. 22189

ctn qty. 10 / 1.2m

PS VK17/30G

EDP-No. 22190

ctn qty. 10 / 3.0m



Scart connection, 21pin.

Scart plug <-> Scart plug

- Gold plated
- For connection of 2 devices with Scart sockets
- Colour: blue transparent

PS LHQB 12

EDP-No. 22196

ctn qty. 20 / 1.2m



Video connections

Scart connection, 21 pin.

Scart plug <-> Scart plug

- Colour: dark blue, metal plug
- For connection of 2 devices with Scart sockets
- Protective cap for contacts

Scart distributor

2x (3x / 5x) Scart socket -> Scart plug

- For connection of 2, 3 or 5 devices with Scart socket and a TV
- Included 0.20m connection lead

HDMI® connection

HDMI® plug <-> HDMI® plug

- For connection of devices with HDMI® sockets
- Supports Audio Return Channel
- Transfer rate up to 5Gbps, 720p/1080i

High Speed HDMI® cable

HDMI® plug <-> HDMI® plug

- For connection of devices with HDMI® sockets
- 3D – Supports 3D resolutions via HDMI® up to 1080p (Dual Stream)
- 4K – For highest resolutions from 4096 x 2160p @ 24Hz
- Supports Audio Return Channel (ARC)
- Transfer rate >10Gbps
- Gold-plated contacts

SAT - LISTED

High Speed HDMI® cable

HDMI® plug <-> HDMI® plug

- For connection of devices with HDMI® sockets
- 3D – Supports 3D resolutions via HDMI® up to 1080p (Dual Stream)
- 4K – For highest resolutions from 4096 x 2160p @ 24Hz
- Supports Audio Return Channel (ARC)
- Transfer rate >10Gbps
- Gold-plated contacts

High Speed HDMI® cable

HDMI® plug <-> HDMI® plug

- For connection of devices with HDMI® sockets
- 3D – Supports 3D resolutions via HDMI® up to 1080p (Dual Stream)
- 4K – For highest resolutions from 4096 x 2160p @ 24Hz
- Supports Audio Return Channel (ARC)
- Transfer rate >10Gbps
- Gold-plated contacts

PS HTSS111

EDP-No. 21460

ctn qty. 10 / 1.5m



PS L 921

EDP-No. 19362

ctn qty. 10 / 2 Scart sockets

PS L 931

EDP-No. 19364

ctn qty. 10 / 3 Scart sockets

PS L951

EDP-No. 19363

ctn qty. 10 / 5 Scart sockets



PS HDHD/09-N

EDP-No. 42930

ctn qty. 10 / 0.9m

PS HDHD/1,5

EDP-No. 22145

ctn qty. 10 / 1.50m



PRO HDHD/15-13

EDP-No. 26849

ctn qty. 10 / 1.50m



PS HDHD 15 SAT

EDP-No. 44900

ctn qty. 10 / 1.50m

PS HDHD 30 SAT

EDP-No. 44901

ctn qty. 10 / 3.0m



PS HDHD/15-13

EDP-No. 42900

ctn qty. 10 / 1.50m

PS HDHD/30-13

EDP-No. 42901

ctn qty. 10 / 3.0m

PS HDHD/50-13

EDP-No. 42902

ctn qty. 10 / 5.0m



Video connections

High Speed HDMI® cable

HDMI® plug <-> HDMI® plug

- For connection of devices with HDMI® sockets
- 3D – Supports 3D resolutions via HDMI® up to 1080p (Dual Stream)
- 4K – For highest resolutions from 4096 x 2160p @ 24Hz
- Supports Audio Return Channel (ARC)
- Transfer rate >10Gbps
- Gold-plated contacts
- Nylon braid

SAT - LISTED

High Speed HDMI® cable

HDMI® plug <-> HDMI® plug

- For connection of devices with HDMI® sockets
- 3D – Supports 3D resolutions via HDMI® up to 1080p (Dual Stream)
- 4K – For highest resolutions from 4096 x 2160p @ 24Hz
- Supports Audio Return Channel (ARC)
- Transfer rate >10Gbps
- Gold-plated contacts
- Nylon braid

High Speed HDMI® cable

HDMI® plug <-> HDMI® plug

- For connection of devices with HDMI® sockets
- 3D – Supports 3D resolutions via HDMI® up to 1080p (Dual Stream)
- 4K – For highest resolutions from 4096 x 2160p @ 24Hz
- Supports Audio Return Channel (ARC)
- Transfer rate >10Gbps
- Gold-plated contacts
- Nylon braid
- Full metal plug

High Speed HDMI® cable with Ethernet

HDMI® plug <-> HDMI® plug

- For connection of devices with HDMI® sockets
- HDMI® Ethernet Channel (HEC) with up to 100Mb/s
- Supports Audio Return Channel (ARC)
- 3D – Supports 3D resolutions via HDMI® up to 1080p (Dual Stream)
- 4K – For highest resolutions from 4096 x 2160p @ 24Hz
- Transfer rate >10Gbps
- Gold-plated contacts
- Nylon braid
- Full metal plug

HDMI® / DVI connection lead

HDMI® plug <-> DVI plug

- For connection of devices with HDMI® socket at devices with DVI socket

PRO HDHD/15-13N2

EDP-No. 42918

ctn qty. 10 / 1.5m



PS HDHD 15 NY SAT

EDP-No. 44902

ctn qty. 10 / 1.5m



PRO HDHD 1.3/1,5

EDP-No. 22338

ctn qty. 10 / 1.5m

PRO HDHD 1.3/3,0

EDP-No. 22345

ctn qty. 10 / 3.0m



PRO HDHD 1.4/1,5

EDP-No. 42914

ctn qty. 10 / 1.5m

PRO HDHD 1.4/3,0

EDP-No. 42915

ctn qty. 10 / 3.0m

PRO HDHD 1.4/5,0

EDP-No. 42917

ctn qty. 10 / 5.0m



PS HDDV/1,5

EDP-No. 22146

ctn qty. 10 / 1.5m



Aerial connections

TV / Radio aerial connection, 75dB

Coaxial plug <-> Coaxial socket

- For connection of TV or radio devices
- 75 ohm coaxial cable
- Double shielded

Antenna connection with ferrite rings, 90dB

Coaxial plug <-> Coaxial socket

- Colour: dark blue
- For connection of TV or radio devices
- Perfect picture by ferrites core and shielding
- Metal plugs, gilded contact surfaces
- 75 ohm coaxial cable
- Double shielded

Antenna connection with ferrite rings, 110dB

Coaxial plug <-> Coaxial socket

- Colour: black
- For digital TV HDTV, for TVs with 100Hz / 200Hz technology
- Inner wire 100% OFC
- Screening efficiency: 110dB
- Triple shielded
- Contacts gold plated

Antenna connection with ferrite rings, 110dB

Coaxial plug <-> Coaxial socket

- Colour: white
- For digital TV HDTV, for TVs with 100Hz / 200Hz technology
- Inner wire 100% OFC
- Screening efficiency: 110dB
- Triple shielded
- Contacts gold plated

Receiver connection, 75dB

F plug <-> F plug

- For connection of e.g. a SAT receiver and a SAT aerial socket with F socket
- Double shielded
- 75 ohm

PS L 715

EDP-No. 19317

ctn qty. 10 / 1.5m

PS L 7138

EDP-No. 19358

ctn qty. 12 / 3.0m

PS L 717

EDP-No. 19321

ctn qty. 10 / 5.0m

PS L 718

EDP-No. 19322

ctn qty. 10 / 10.0m

PS L719

EDP-No. 43905

ctn qty. 5 / 15.0m



PS HTCPCJ01

EDP-No. 22071

ctn qty. 10 / 1.5m

PS HTCPCJ03

EDP-No. 22072

ctn qty. 10 / 3.0m

PS HTCPCJ05

EDP-No. 22073

ctn qty. 10 / 5.0m



PS L7110 15BS

EDP-No. 43900

ctn qty. 10 / 1.5m



PS L7110 15WS

EDP-No. 43903

ctn qty. 10 / 1.5m



PS STC FV15C

EDP-No. 19345

ctn qty. 10 / 1.5m

PS STC FV30C

EDP-No. 19346

ctn qty. 10 / 3.0m



Aerial connections

Coaxial cable, 75dB

- Double shielded
- Screening attenuation: 75dB
- For connections for SAT TV, cable and terrestrial systems

PS KX 710-10

EDP-No. 19415

ctn qty. 10 / 10.0m

PS KX 710-15

EDP-No. 19416

ctn qty. 5 / 15.0m

PS KX 710-20

EDP-No. 19417

ctn qty. 5 / 20.0m

PS KX 710-30


EDP-No. 19418

ctn qty. 5 / 30.0m

PS KX 710-40

EDP-No. 19419

ctn qty. 4 / 40.0m



PC connections – USB

USB 2.0 compatible connection

USB type A plug <-> USB type B plug

- Assorted colours: silver, blue, red
- Connects a PC/USB-Hub with devices such as Scanner, Printer, etc.
- Compatible to the USB 2.0 standard
- Up to 480 Mbs data rate

PS B/CK151/1A

EDP-No. 22854

ctn qty. 30 / 1.5m



USB 2.0 compatible connection, grey

USB type A plug <-> USB type B plug

- Connects a PC/USB-Hub with devices such as Scanner, Printer, etc.
- Compatible to the USB 2.0 standard
- Up to 480 Mbs data rate

PS B/CK15/18

EDP-No. 25407

ctn qty. 10 / 1.8m

PS B/CK 15/3

EDP-No. 22227

ctn qty. 10 / 3.0m

PS B/CK 15/5

EDP-No. 22228

ctn qty. 10 / 5.0m



USB 2.0 compatible connection, translucent

USB type A plug <-> USB type B plug

- Connects a PC/USB-Hub with devices such as Scanner, Printer, etc.
- Compatible to the USB 2.0 standard
- Up to 480 Mbs data rate

PS B/CK16/18

EDP-No. 25408

ctn qty. 10 / 1.8m

PS B/CK16/30

EDP-No. 25409

ctn qty. 10 / 3.0m



PC connections – USB

USB 2.0 compatible connection

USB type A plug <-> USB type B plug

- For connecting PCs/laptops to periphery devices, e.g. printers, scanners etc.
- Compatible to the USB 2.0 standard
- Cable surface out of nylon netting
- With gold contacts, for data transfer with the lowest possible levels of interference
- High speed data transfer rate of up to 480Mbps

USB 2.0 certified connection, translucent

USB type A plug <-> USB type B plug

- Connects a PC/USB-Hub with devices such as Scanner, Printer, etc.
- Certified in line with USB 2.0 standard
- Up to 480 Mbs data rate

USB 2.0 certified connection

USB type A plug <-> USB type B plug

- Connects a PC/USB-Hub with devices such as Scanner, Printer, etc.
- Cable surface out of nylon netting
- Certified in line with USB 2.0 standard
- Up to 480 Mbs data rate

USB 2.0 compatible connection

USB type A plug <-> USB type mini B plug

- For connecting the PC / laptop to peripheral devices, e.g. HUBs, digital cameras, MP3 players, with a mini USB connection
- To USB 2.0 standard compatible
- High speed data transfer rate of up to 480Mbps

USB 2.0 compatible extension

USB type A plug <-> USB type A socket

- For the extension of existing cable or for the comfortable connection of terminal equipment with USB type A interfaces
- Compatible with the USB 2.0 Standard
- High Speed data transfer rate of up to 480Mbps

PS CC U 18

EDP-No. 26206

ctn qty. 10 / 1.8m



PS B/CK17/18

EDP-No. 25411

ctn qty. 10 / 1.8m



PS B/CK17/30

EDP-No. 25412

ctn qty. 10 / 3.0m



PS CC U2 18

EDP-No. 26799

ctn qty. 10 / 1.8m



PS B/CK18/18

EDP-No. 25413

ctn qty. 10 / 1.8m



PS B/CK19/18

EDP-No. 25414


ctn qty. 10 / 1.8m



PS B/CK 19/30

EDP-No. 26794

ctn qty. 10 / 3.0m



PC connections – Cat 5e Network

Cat 5e network connection

RJ45 plug <-> RJ45 plug

- Assorted colours: silver, blue, red
- Twisted Pair Network lead
- 1:1 wiring
- For connections between Hubs/Switches and PC's
- Single shielded
- Fully shielded plug

PS B/CK 132/2

EDP-No. 22267

ctn qty. 30 / 2.0m



PC connections – Cat 5e Network

CAT 5e network connection

RJ45 plug <-> RJ45 plug

- Twisted Pair Network lead
- 1:1 wiring
- For connections between Hubs/Switches and PC's
- Single shielded
- Fully shielded plug

CAT 5e crossover network connection

RJ45 plug <-> RJ45 plug

- Twisted Pair Network lead
- Crossover wiring
- For connections between two PC's
- Single shielded
- Fully shielded plug

PS B/CK 132/2

EDP-No. 20241

ctn qty. 10 / 2.0m

PS B/CK 132/5

EDP-No. 20242

ctn qty. 10 / 5.0m

PS B/CK 132/10

EDP-No. 20243

ctn qty. 10 / 10.0m

PS B/CK 132/15

EDP-No. 20244

ctn qty. 10 / 15.0m

PS B/CK 132/20

EDP-No. 20245

ctn qty. 10 / 20.0m

PS B/CK 132/25

EDP-No. 20246

ctn qty. 5 / 25.0m

PS B/CK 132/30

EDP-No. 20247

ctn qty. 5 / 30.0m

PS B/CK 132/40

EDP-No. 20248

ctn qty. 5 / 40.0m



PC connections – Monitor

Monitor connection

HD 15pin. plug <-> HD 15pin. plug

- Single shielded
- 1:1 VGA connection

Monitor extension lead

HD 15pin. plug <-> HD 15pin. socket

- Single shielded
- 1:1 VGA connection

PS B/CK74

EDP-No. 19337

ctn qty. 10 / 1.8m

PS B/CK75

EDP-No. 19338

ctn qty. 10 / 1.8m



PC connections – Power

Power lead

Schuko plug - 3 pin. IEC plug

- Non-heating appliance
- Mains connection for e.g. a PC
- With security contact

PS B/CK 80/20

EDP-No. 19384

ctn qty. 10 / 1.8m



PC connections – Audio/Video

High Speed HDMI® cable

HDMI® plug <-> HDMI® plug

- For connection of devices with HDMI® sockets
- 3D – Supports 3D resolutions via HDMI® up to 1080p (Dual Stream)
- 4K – For highest resolutions from 4096 x 2160p @ 24Hz
- Supports Audio Return Channel (ARC)
- Transfer rate >10Gbps
- Gold-plated contacts

PS B/CK77

EDP-No. 26796

ctn qty. 10 / 1.5m



DVI-D, single link connection cable

DVI-D plug <-> DVI-D plug

- Monitor DVI digital single-link connection lead for connection of a monitor with DVI digital bus to a graphics card with similar connection
- Data transfer rate up to 4.95Gbit
- Double shielded lead
- Fully shielded plug

PS B/CK76

EDP-No. 26795

ctn qty. 10 / 1.8m



Telephone connections and adapters

TAE F connection

TAE-F plug <-> RJ11 plug

- For telephones with 2-cores
- Colour: black

PS LTK5a

EDP-No. 19404

ctn qty. 10 / 6.0m



Telephone extension

TAE-F plug <-> TAE-F socket

- 4-core
- Colour: black

PS LTK15a

EDP-No. 19397

ctn qty. 10 / 6.0m



PS LTK15c

EDP-No. 19398

ctn qty. 10 / 10.0m



Fax/Modem extension


TAE-N plug <-> TAE-N socket

- 6-core
- Colour: black

PS LTK16c

EDP-No. 19400

ctn qty. 10 / 10.0m



Wall socket extension

TAE-F plug <-> TAE-F/F/N socket

- TAE-F plug
- Triple socket TAE N/F/F

PS LTA18

EDP-No. 19395

ctn qty. 10 / 0.2m